

 SpeakerCraft®



## *Profile™*

Profile is the best-looking line of speakers we've ever created. Really, Profile is the least-looking line of speakers we've ever created. They barely even look like speakers. They look more like shadows—and that's if you notice them at all, which no one probably will unless they're just insatiably curious about where all that great sound is coming from.

There's no bezel and no visible mounting flange. All you see is a grille, which can be painted to match the wall or ceiling. It's the cleanest speaker installation you ever saw—or didn't see.

The Profile concept is available in numerous SpeakerCraft products. It's perfect for any place you want great sound but don't want visible speakers—in other words, for any room of any house in the world.



U.S. Patent No. D419,591 & 6,101,262

## Profile AIM8 One

- Flangeless Appearance
- Pivoting and Rotating 8" Injection Molded Polypropylene Cone Woofer
- Pivoting 1" Treated Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers
- Sensitivity: 88dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohms
- Frequency Response: 40Hz - 20kHz



## Profile CRS6 One

- Flangeless Appearance
- 6½" Polypropylene Cone Woofer with Rubber Surround
- Pivoting 1" Liquid Cooled Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers
- Sensitivity: 92dB 1W/1m
- Power Handling: 100 Watts
- Impedance: 8 Ohms
- Frequency Response: 40Hz - 20kHz



U.S. Patent No. D419,591 & 6,101,262

## Profile AIM7 Two

- Flangeless Appearance
- Pivoting and Rotating 7" Resin Reinforced Fiberglass Cone Woofer
- Pivoting 1" Silk Dome Tweeter
- Timbre-Matched to All Two Series Speakers
- Front-Mounted Treble Equalization Switch
- Sensitivity: 90dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohms
- Frequency Response: 40Hz - 20kHz



## Profile CRS3

- Flangeless Appearance
- Small Footprint In-Ceiling
- 3" Full Range Aluminum Cone Woofer
- Timbre-Matched to All Three Series Speakers
- Sensitivity: 86dB 1W/1m
- Power Handling: 40 Watts
- Impedance: 8 Ohms
- Frequency Response: 80Hz - 16kHz



U.S. Patent No. D419,591 & 6,101,262

## Profile AIM5 One

- Flangeless Appearance
- Pivoting and Rotating 5 ¼" Injection Molded Polypropylene Cone Woofer
- Pivoting ¾" Treated Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers
- Sensitivity: 88dB 1W/1m
- Power Handling: 75 Watts
- Impedance: 8 Ohms
- Frequency Response: 55Hz - 20kHz



U.S. Patent No. 7,522,742 B2

## Profile AIM LCR One

- Flangeless Appearance
- Pivoting Woofer Baffle
- Two 5¼" Injection Molded Graphite Cone Woofers with Phase Plugs
- Pivoting 1" Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers
- Sensitivity: 89dB 1W/1m
- Power Handling: 80 Watts
- Impedance: 8 Ohms
- Frequency Response: 55Hz - 20kHz



## Profile CRS8 One

- Flangeless Appearance
- 8" Polypropylene Cone Woofer
- Pivoting 1" Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers
- Sensitivity: 89dB 1W/1m
- Power Handling: 100 Watts
- Impedance: 8 Ohms
- Frequency Response: 40Hz - 20kHz



U.S. Patent No. 7,522,742 B2

## Profile AIM LCR3 Three

- Flangeless Appearance
- Pivoting Woofer Baffle
- Two 3" Aluminum Cone Woofers with Phase Plugs
- Pivoting ¾" Aluminum Dome Tweeter
- Front-Mounted 2-Position Treble Adjustment Switch
- Timbre-Matched to All Three Series Speakers
- Sensitivity: 86dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohms Compatible
- Frequency Response: 78Hz - 20kHz

\* All Profile Speakers come with Limited LIFETIME Warranty

\* As we incorporate design improvements, specifications may change without notice.



940 Columbia Ave., Riverside CA 92507 • USA (800) 448 0976 Fax (951) 787 8747 International +1 951 787 0543 • www.speakercraft.com